

# KR310

## Dual frequency RFID waterproof reader



KR310 is an external wiegand reader for ZKTeco access control standalone devices and control panels. With a robust design, it is easy to connect and install, and offer the possibility to control one door from both sides. The LED lights indicate allowed or denied access. It has a proximity reading range of up to 10cm (125KHz). KR310 is waterproof, and the operating temperatures can range from -10° to +70°, it is the ideal solution for outdoor installation.

### Features

- IP65 waterproof
- Dual Frequency (125kHz / 13,56MHz)
- Compatible with ID, Mifare Classic, Mifare Desfire
- 34 bit

### Specifications

|                       |                                                                  |
|-----------------------|------------------------------------------------------------------|
| Compatibility         | ID, Mifare Classic, Mifare Desfire                               |
| Wiegand Signal        | Wiegand 34 bit (EM/MF)                                           |
| Power Supply          | DC 6-14V / Max.70mA                                              |
| Reading Distance      | Up to 10cm (According to different working conditions and cards) |
| Read Time             | <300ms                                                           |
| Operating Frequency   | 125KHz / 13.56MHz                                                |
| Operating Temperature | -10 °C- 70 °C                                                    |
| Operating Humidity    | 10%-90%                                                          |
| Dimension(LxWxH)      | 77,5x42,8x16,5 mm                                                |

### Dimensions (mm)

